



CARBIFLO SLAB




TECHNICALS SPECIFICATIONS

CODE	DESCRIPTION	COLOR	DIMENSIONS	WEIGHT (LB)	MPa	UN/PAL
TURFG	TURFSTONE	Steel gray	3 $\frac{1}{8}$ x 15 $\frac{3}{4}$ x 15 $\frac{3}{4}$	37.5 lb	50	40
ECO-TURFG	TURFSTONE	Steel gray	3 $\frac{1}{8}$ x 15 $\frac{3}{4}$ x 15 $\frac{3}{4}$	37.5 lb	50	40

 Each project must be designed and validated by a professional engineer, based on soil conditions and expected loads.

 Acceptable applications include emergency vehicle access and occasional truck use, with a maximum lifetime ESAL load limit of 7,500.

 The Turfstone product is designed to resist freezing, deformation under load, and bad weather thanks to its permeable grid design.



PALET

Number of rows	1 row	1 palet	Weight per square foot
10	6,88 sq ft	68,8 sq ft	22 lb / sq ft

INSTALLATION RECOMMENDATIONS

 Requires an aggregate base, compacted to 95-98% standard Proctor density, thickness varying between 8 to 16 inches depending on soil type.

 Use of a drainage geotextile recommended.